



Main Features

- 🔔 Warrior black paint colour scheme with badges
- 🔔 Stainless steel exhaust
- 🔔 Deutz Tier 3- 246 Hp 6.1 Lt Turbocharged engine with 981nm max torque
- 🔔 NO AdBlue + DPF
- 🔔 50km/h TTV variable speed transmission
- 🔔 MaxiVision II deluxe cabin with Automatic climate control + carpet floor mat
- 🔔 MaxCom armrest control
- 🔔 Full work light package with 14 work lights
- 🔔 Grammer Max Dynamic Plus XXL seat with dynamic dampening, heater + swivel
- 🔔 Mechanical cabin suspension
- 🔔 Dynamic front axle suspension with 120 mm travel
- 🔔 120 L/min Closed centre hydraulics fitted with 4 Sets of rear remotes
- 🔔 Power beyond and load sense lines
- 🔔 4 Speed PTO
- 🔔 EasySteer hydraulic steering system fitted with Trimble GFX750 Precision Ag system – RangePoint Ready
- 🔔 ISOBUS 11783 UT connectivity
- 🔔 ComforTip Headland management
- 🔔 Front Linkage + PTO (1000 Speed)
- 🔔 Comfort pack front hydraulics – Includes 1 set of front remotes and external linkage controls
- 🔔 3yr/2500hrs Warranty

August 2021

Engine

Deutz TCD6_1 LO6 4V Tier 3 Diesel Engine
 6 Cyl/6057cc Turbocharged/Intercooled
 NO AdBlue and DPF
 Electronically Controlled
 4 Valves Per Cylinder
 Liquid/Oil Cooled
 Common Rail DCR Injection System
 246Hp Max Power (ECE R-120)
 9Hp Power Boost
 Max Torque 981nm @1600 rpm
 Engine Speed Programming x 2
 Powercore Air Filter with Dust Ejectors
 Side Exhaust
 435Lt Fuel Capacity

Transmission

ZF S-Matic 240HD CVT Transmission
 4 Working Ranges
 3 Driving Modes (Auto, PTO, Manual)
 Acceleration and Power Adjustment
 Speed Cruise Control x 2
 Active Stationary Control
 Wet Clutch Powershuttle
 Shuttle Modulation – 5 Stage (Sense Clutch)
 Front Wheel Assist
 4 Wheel Braking with Power Brake System
 Front Axle Suspension with Adaptive Damping System
 Front & Rear Diff Lock
 ASM Auto Diff Lock and 4wd Engagement
 Radar
 Separate Transmission Fluid Reservoir
 50 km/h Road Speed @ Economy RPM 1969 rpm

PTO

Independent Wet Multidisc Clutch
 3 Speed PTO 540E/1000/1000E
 Push Button Control on Armrest
 Auto PTO
 External PTO Start/Stop
 Interchangeable PTO Spline Function
 1" 3/8 – 6 Spline PTO Shaft
 1" 3/8 – 21 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Radial Wheel Equipment
 540/65R34 Front -710/70R38 Rear
 Dynamic Front Fenders
 Warrior Brilliant Black Paint + Decals
 Stainless Steel Exhaust

Weights & Dimensions

Wheelbase	2868mm
Length	4575mm
Total Height	3173mm
Total Weight	9100 kg

Operator Environment

MaxiVision 2 Air Conditioned Cab
 Automatic Climate Control
 Mechanical Cabin Suspension
 Cab Roof Hatch without Glass
 Double Glazed Rear Lower Cab Glass
 Max Comfort Dynamic XXL Deluxe Air Seat with swivel
 INFOCENTER Pro Digital Display
 WORK Monitor
 MaxCom Armrest Controls - Adjustable
 COMFORTIP Sequential Drive System
 Padded Trainee Seat with Seatbelt
 EASY STEER Quick Steer System
 Bluetooth MP3 Audio System
 WOLP (Work Operating Light Panel)
 2 External Electric Heated Mirrors
 Courtesy LED Entry Light
 Hi Beam / Low Beam Bonnet +Cab Post Lights
 2 Bonnet Front Work Lights
 8 Cabin Work Lights
 2 Front Work Lights on Cab Post
 2 Rear Work Lights on Cab Post
 Rotating Beacon

Connected Farming Systems

EASY STEER Hydraulic Auto Steer
 Trimble GFX750 with NAV 900
 RangePoint + UT Ready
 ISOBUS 11783 9 pin socket + Internal cab socket
 ISO 11786 7pin socket

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
 160 L/min Hyd Pump
 Power Beyond Valve and Load Sensing Lines
 Hi Flow & Free Flow Return
 Separate 42L/min Steering Pump
 4 Sets of Electro-Hyd Remotes
 Flow and Timer Control on All Remotes
 External Push Buttons on Guard for 1 Remote
 AGROTRONIC EHR with Position & Draft
 Implement Ride Control
 External Raise & Lower on Rear Fenders
 Cat II/III Hook Ends
 10000 kg Lift Capacity
 Swinging Drawbar – CAT 3

Front Linkage & PTO

Front Linkage - 5480kg Capacity
 Front PTO – 1000N
 1 Front Remote & External Raise/Lower
 Dial Control to Operate Front Linkage