



## Main Features

- 🔔 Warrior black paint colour scheme with badges + Stainless steel exhaust
- 🔔 Deutz Tier 3- 336 Hp 7.8 Lt Twin Turbo engine with 1372nm max torque
- 🔔 NO AdBlue + DP
- 🔔 60km/h TTV variable speed transmission
- 🔔 4 Wheel Braking with front dry disc brakes
- 🔔 Hydraulic trailer brakes
- 🔔 MaxiVision II deluxe cabin with automatic climate control + carpet floor mat
- 🔔 MaxCom armrest control
- 🔔 Full work light package with 14 work lights + LED Bonnet lights
- 🔔 Grammer Max Dynamic Plus XXL seat with dynamic dampening, heater + swivel
- 🔔 Pneumatic cabin + Dynamic front axle suspension
- 🔔 210 L/min Closed centre hydraulics fitted with 4 Sets of rear remotes
- 🔔 Power beyond and load sense lines
- 🔔 IF Wheel equipment fitted with 820kg rear wheel weights
- 🔔 EasySteer hydraulic steering system fitted with Trimble GFX750 Precision Ag system – RangePoint Ready
- 🔔 ISOBUS 11783 UT connectivity
- 🔔 ComforTip Headland management
- 🔔 Front Linkage fitted with 1400kg weight +1000 Speed PTO
- 🔔 Comfort pack front hydraulics – Includes 1 set of front remotes and external linkage controls
- 🔔 3yr/2500hrs Warranty

August 2021

## Engine

Deutz TTCD 7.8 LO6 Tier 3 Diesel Engine  
 6 Cyl/7775cc Twin Turbocharged/Intercooled  
 NO AdBlue  
 Electronically Controlled  
 4 Valves Per Cylinder  
 Liquid/Oil Cooled  
 Common Rail DCR Injection System  
 Electronically Controlled E-Visco Fan  
 336 hp Max Power (ECE R-120)  
 20Hp Power Boost  
 Torque 1372nm  
 Engine Speed Programming × 2  
 Powercore Air filter with Dust Ejectors  
 Side Exhaust  
 600 Lt Fuel Capacity

## Transmission

ZF Terramatic CVT Transmission  
 4 Working Ranges  
 3 Driving Modes (Auto, PTO, Manual)  
 Acceleration and Power Adjustment  
 Speed Cruise Control × 2  
 Active Stationary Control  
 Wet Clutch Powershuttle  
 Shuttle Modulation – 5 Stage (Sense Clutch)  
 Front Wheel Assist  
 4 Wheel Braking with Power Brake System  
 Front Dry Disc Brakes  
 Front Axle Suspension  
 Hydraulic Trailer Braking  
 Front & Rear Diff Lock  
 ASM Auto Diff Lock and 4wd Engagement  
 Radar  
 Separate Transmission Fluid Reservoir  
 60 km/h Road Speed @ Economy RPM

## PTO

Independent Wet Multidisc Clutch  
 3 Speed PTO 540E/1000/1000E  
 Push Button Control on Armrest  
 Auto PTO  
 External PTO Start/Stop  
 1"3/4 20 Spline PTO Shaft  
 Interchangeable PTO Spline Function

## Wheel Equipment & Miscellaneous

Fixed Radial Wheel Equipment  
 600/70R34 Front -800/70R42Rear  
 IF – Hi Flex Tyre Equipment  
 Rear 820kg Wheel Weights  
 Dynamic Front Fenders  
 Warrior Brilliant Black Paint + Decals  
 Stainless Steel Exhaust

## Operator Environment

MaxiVision 2 Air Conditioned Cab  
 Automatic Climate Control  
 Pneumatic Cabin Suspension  
 Cab Roof Hatch Without Glass  
 Double Glazed Rear Lower Cab Glass  
 Max Comfort Dynamic XXL Deluxe Air Seat with Swivel  
 INFOCENTER Pro Digital Display  
 WORK Monitor  
 MaxCom Armrest Controls - Adjustable  
 COMFORTIP Sequential Drive System  
 Padded Trainee Seat with Seatbelt  
 EASY STEER Quick Steer System  
 Bluetooth MP3 Audio System  
 WOLP (Work Operating Light Panel)  
 2 External Electric Heated Mirrors  
 Courtesy LED Entry Light  
 Hi Beam / Low Beam Bonnet + Cab Post Lights  
 2 Bonnet Front Work Lights  
 8 Cabin Work Lights  
 2 Front Work Lights on Cab Post  
 2 Rear Work Lights on Cab Post  
 Rotating Beacon

## Connected Farming Systems

EASY STEER Hydraulic Auto Steer  
 Trimble GFX750 with NAV 900  
 RangePoint + UT Ready  
 ISOBUS 11783 9 pin socket + Internal cab socket  
 ISO 11786 7pin socket

## Hyd/Linkage/Drawbar

Closed Centre Hydraulic System  
 210 L/min Hyd Pump  
 Power Beyond Valve  
 Separate 42L/min Steering Pump  
 Separate Hydraulic Fluid Reservoir  
 4 Sets of Electro-Hyd Remotes  
 Flow and Timer Control on All Remotes  
 AGROTRONIC EHR with Position & Draft  
 Implement Ride Control  
 External Raise & lower on Rear Fenders  
 Cat III Hook Ends  
 12000 kg lift Capacity  
 Swinging Drawbar - CAT 4

## Front Linkage & PTO

Front Linkage - 5000kg Capacity  
 Front PTO – 1000N  
 1 Front Remote & External Raise/Lower  
 Dial Control to operate front linkage  
 FP-PAC quick attach front weight(1400kg)

## Weights & Dimensions

|              |         |
|--------------|---------|
| Wheelbase    | 3153mm  |
| Length       | 5268mm  |
| Total Height | 3500mm  |
| Total Weight | 14820kg |