

5125G Heavy Duty

Engine

FARMotion Tier 4i Diesel Engine 4 Cyl/3849cc Turbocharged/Intercooled Electronically Controlled Emission Control by DOC Unit Liquid/Oil Cooled with Fixed Fan High Pressure Diesel Injection/Common Rail 126 Max Hp @ 2200 rpm (2000/25/CE) 6 Hp Power Boost Torque 500 Nm @1600 rpm Engine Speed Programming × 2 Powercore Air Filter with Dust Ejectors Side Vertical Exhaust Fuel Tank 150 litres

Transmission

60/60 Forward/Reverse Gears Sense Clutch Wet Clutch Powershuttle Shuttle Modulation with 5 Settings 5 Speeds / 4 Ranges / 3 Stage Powershift Speed Matching Comfort Clutch Stop and Go Function Front Wheel Assist - Push Button 4 Wheel Independent Braking 100% Front & Rear Diff Lock - Push Button 40 km/h Road speed @ Super Economy RPM

PTO

Independent Wet Multidisc Clutch 4 Speed PTO 540/540E- 1000/1000E Push Button Control in Cab/Rear Fender Interchangeable PTO Spline Function 1" 3/8 - 6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment 440/65R28 Front -540/65R38 Rear Tyres Front Weight Frame 12v elec, socket and 7-pin ISO 11786 plug Deutz-Fahr STOLL Loader Ready includes; Subframe Hydraulic Kit Joystick with Powershift buttons Electrical switches for loader operation



Operator Environment

D2L Class Air Conditioned Cab Hydro Silent Block Cabin Suspension Super Deluxe Air Seat Tilt and Telescopic Steering Wheel SDD Rapid Steering Circuit Hi Visibility Polycarbonate FOPS Roof INFOCENTER II Digital Display MP3 Radio Player with Twin Speakers Telescopic Mirrors 4 Cabin Work Lights 2 Bonnet Front Work Lights 2 Duplicate Headlights on Cab Post 2 Work lights on Cab Post Rotating Beacon

Hyd/Linkage/Drawbar

90 L/min On Demand Hydraulic System Separate 40L/min Steering Pump 3 Sets of Remotes - 3 Detent / 3 Float Flow Control on All Valves Electronic Hitch with Position & Draft Control Free flow Return Line External Raise & lower on Rear Fenders Cat 2 Hook ends-telescopic stabilisers 5410 kg lift capacity with Assistor Rams Swinging Drawbar - CAT A

Weights & Dimensions

Wheelbase 2400 mm Length 4314 mm Total Height 2730mm Total Weight 4400kg