

6140 TTV 50km/h Variable

Engine

FARMotion Tier 4i Diesel Engine 4 Cyl/3849cc Turbocharged/Intercooled **Electronically Controlled** No AdBlue / No DPF Liquid/Oil Cooled with Viscous Fan High Pressure Diesel Injection Common Rail 136 Max Hp @ 2200 rpm (2000/25/CE) 6Hp Power Boost Torque 544 Nm @1600 rpm Engine Speed Programming × 2 Powercore Air Filter with Dust Ejectors Side Vertical Exhaust Fuel Tank 200 Litres

Transmission

TTV 2 range Variable Transmission 3 Modes (AUTO, Manual, PTO) Eco/Power Dial Speed Cruise Control × 2 Active Stationary Control (Power Zero) Wet Clutch Powershuttle Shuttle Modulation - 5 Stage (Sense Clutch) Front Wheel Assist - Push Button 4 Wheel Independent Braking Hydraulic Parking Brake (HPB) 100% Front & Rear Diff Lock - Push Button ASM Auto Diff Lock & 4WD Engagement Front Axle Suspension 50km/h Road Speed

PTO

Independent Wet Multidisc Clutch 3 Speed PTO 540/540E/1000 Push Button Control in Cab/Fender Auto PTO Interchangeable PTO Spline Function 1" 3/8 - 6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment 480/65R28 Front -600/65R38 Rear 2450mm Rear Guard Extensions Pre Arrangement for Front Linkage + PTO Front Weight Frame ISO 11786 7 pin Socket + 12V Socket



Operator Environment

E class Air Conditioned Cab Mechanical Cabin Suspension Max-Professional Air Seat Tilt and Telescopic Steering Wheel SDD Rapid Steering Circuit Hi Visibility Glass Roof INFOCENTER Pro Digital Display COMFORTIP Sequential Drive System Satellite Armrest with MaxCom Joystick 4 Programmable Buttons on MaxCom Joystick Trainee Seat with Seatbelt MP3 Radio Player with Quad Speakers Telescopic Mirrors WOLP (Work Operating Light Panel) 8 Cabin Work Lights 2 Work Lights on Cab Post 4 Bonnet Front Work Lights Rotating Beacon

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System 120 L/min Hyd Pump Power Beyond Valve and load sensing lines Hi Flow & Free Flow return 4 Sets of Electro-Hyd Remotes with Float Timer & Flow Control on All Remotes AGROTRONIC EHR with Position & Draft External Raise & Lower on Rear Fenders Cat II Hook Ends 5000 kg Lift Capacity Swinging Drawbar - CAT A

Weights & Dimensions

Wheelbase 2550 mm Length 4428mm Total Height 2740mm Total Weight 5950kg