

5115 DF TTV

Specialist Series



Engine

FARMotion Tier 4i Diesel Engine 4 Cyl/3849cc Turbocharged/Intercooled Electronically Controlled Emission Control by DOC unit Liquid/Oil Cooled Electronically Controlled E-Visco Fan High Pressure Diesel injection common rail 113 Hp Max hp @ 2200 rpm (2000/25/CE) 6 Hp Power Boost Torque 435 Nm @1600 rpm Programmable Engine Speed × 2 Powercore Air Filter with Dust Ejectors Side Vertical Exhaust Fuel Tank 95 Litres

Transmission

TTV 2 Range Variable Transmission 3 Modes (AUTO, Manual, PTO) Eco/Power Dial Speed Cruise Control × 2 Active Stationary Control (Power Zero) Wet Clutch Powershuttle Shuttle Modulation – 5 Stage (Sense Clutch) Front Wheel Assist – Push Button 4 Wheel Independent Braking Hydraulic Parking Brake (HPB) 100% Front & Rear Diff Lock - Push Button 40km/h Road Speed @ 1650 RPM

PTO

Independent Hydraulic Rear PTO Push Button Auto PTO Function 3 Speed PTO 540/750/1000 1" 3/8 - 6 Spline PTO Shaft Interchangeable PTO Spline Function

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment Front 280/70R20 Rear 380/70R28 Rear Front Weight Frame with 4 Weights (155kg) Rear Swinging Drawbar Battery Isolator Switch

Operator Environment

4 Post Air conditioned Cabin with CAT 4 Filtration Flat Operator Floor Rear Hinged Roof for High Visibility Hydro Silent Block Cabin Suspension Super Deluxe Air Seat with Tilt and Lumbar Support Tilt and Telescopic Steering Wheel Armrest Control with MaxCom Joystick 3 Programmable Buttons on MaxCom Joystick SDD Rapid Steering Circuit INFOCENTER Pro Digital Display **COMFORTIP Sequential Drive System** MP3 Radio Player with Speakers Telescopic Mirrors 6 Cabin Work Lights 4 Bonnet Front Work lights Rotating Beacon 2 External Electrical Sockets

Hyd/Linkage/Drawbar Closed Centre Hydraulic System 100 I/min Hydraulic Pump

Electro Hyd Remotes Controlled on MaxCom Armrest 4 Sets of Rear High Flow Remotes 4 Sets of Front Remotes (8 outlets) 2 Sets Duplicated Hi Flow Remotes at Front (3 Outlets) 2 Return Ports on Front and 1 Return Port on Rear Timer and Flow Control on All Remotes Separate 27L/min Steering Pump Electronic 3PL c/w Position & Draft Controls External Push button Raise and Lower Cat 2 Hook Ends 3800 kg Lift Capacity

Weights & Dimensions

Swinging Drawbar - CAT A

Wheelbase 2174 mm Length 4211 mm Total Height 2495mm (Top of Cab) Min Overall Width 1584mm (Rear wheels) Cabin Width 1130mm Total Weight 3030kg