Specifications

				KUBOTA	
Model				Z411KW-48-AU	Z421KW-54-AU
Engine	Model			GH7302V	GH7301V
	Туре			Air cooled 2 cylinders petrol engine	
	Engine Gross power		HP	22.0 24.0	
	Total displacement		cu.in. (cc)	44.3 (726)	
	Starting system			Key switch	
Dimensions	Overall length m		mm	2055	
	Overall width Overall height	w/ mower	mm	1552	1710
		w/o mower	mm	1236	
		w/ ROPS (upright)	mm	1772	
		w/o ROPS (folded)	mm	1265	
Wheelbase			mm	1255	
Tread/Tyre	Tread	Front	mm	944	
,	Rear mm			1000	
	Tyre size	Front tyre	mm	13 × 5.0 – 6, Smooth pneumatic	
		Rear tyre	mm	24 × 9.5 –14, Low profile tyre	
Weight (w/ mower)		car tyro	kg	394	400
Transmission			9	Hydro-Gear® Comme	
Transmission system				2-HST w/Gear reduction	
Speed control				2-hand lever	
Travelling speed range	Forward		km/h	2-nand lever 0 – 16.0	
navelling speed range	Reverse		km/h	0 – 16.0	
Proking oveter			Cog style parking lock / Foot pedal		
Braking system	Time			Cog style parking lock / Foot pedal Belt drive	
РТО	Type				
	Clutch type			Electric clutch	
	PTO brake			Dry disc	
Mower deck	Model			RCK48P-400Z	RCK54P-400Z
	Mower deck type			Side discharge	
	Mower lift system			Mechanical / Foot pedal	
	Deck depth		mm	127	
	Belt type			Belt drive	
	Deck steel thickness m		mm	3.4	
	Anti scalp roller			Rigid	
	Cutting width of mower		in.	48	54
	Number of blades			3	
	Cutting height		mm	38 – 127	
	Mounting system of mower			Parallel linkage	
	Blade tip speed		FPM (m/s)	18800 (95.5) 18700 (95.0)	
Seat				Suspension	seat
Engine stop system				Key stop	
Fuel tank capacity ℓ			l	25.7	
Battery				U1 (12V, RC: 45min, CCA: 300, CA: 410)	
Generator capacity Amp			Amp	15A	
Hour meter				Standard	
Fuel gauge				Sight wind	OW

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, eminental conditions, maintenance, and other variables.

"Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or UZ723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

Attachment & Option Kit



Grass Catcher

The optional 7 bushels (250) liters) grass catcher can be attached and detached without ever requiring the use of any tools.



©2019 Kubota Corporation

- Mulching Kit
- LED Work Lights
- OCDC
- Maintenance Lift Kit

Kubota

Kubota Australia Pty Ltd

25-29 Permas Way, Truganina VIC, 3029 Australia Freecall: 1800-334-653 Email: sales@kubota.com.au

Web Site: http://www.kubota.com.au

Kubota New Zealand Limited

Freecall: 0800-582-682 Fmail: sales@kubota.com.au

Web Site: http://www.kubota.co.nz





For Earth, For Life Kubota



Cat.No.2444-01-ANZ Printed in Japan.D.REX.'19-DEC.



PERFORMANCE & EASY OPERATION

The Z400 Series boasts the kind of performance found only in commercialgrade mowers, as well as the easy operation that residential and professional users alike can appreciate.



The Z400 Series comes equipped with powerful KAWASAKI engines that provide the torque you need to power through tall grass and rugged environments.

RUGGED TRANSMISSION

Power from the engine is delivered to the wheels through rugged, Hydro-Gear® Commercial ZT3600® transmission.



PRECISION ADJUSTMENT

A simple twist of a dial lets you adjust the cutting height in precise 1/4" increments.



PARKING BRAKE

A foot pedal locks the brake so the unit can't move, ensuring safe and secure parking.





FOLDABLE ROPS

The ROPS on the Z400 Series mowers meets ISO 21299 specifications to ensure safe and efficient operation. The ROPS easily folds down to allow the mower to pass under low obstructions, as well as permits easier storage in a garage or shed.

KUBOTA

24" Rear Tyres
Big tyres mean a softer ride.

Operator Controlled Discharge Chute.

LOW PROFILE TYRE

The Z400 Series' new wide low-profile tyres not only look good, they provide better traction for all types of mowing tasks. They also have a larger footprint that reduces ground compaction as well as turf damage during turns.

KALIFIE **Mechanical One Push Deck** Lift Pedal

The K-Lift pedal lets you quickly and easily adjust the cutting height without leaving your seat. Simply press the pedal and turn the adjustment dial!



Push and release the pedal to raise the deck



Use the dial to adjust the cutting height



Push and release the pedal again to lower the deck

COMFORT AND CONVENIENCE

Designed for performance, the Z400 Series also offers a wealth of comfort and convenience features to keep you feeling fresh and working longer.

12V POWER OUTLET

Charge your phone or other accessory while mowing the lawn. The Z400 also has an integrated smart phone holder.



HIGH BACK SUSPENSION SEAT & 152 mm SLIDE SEAT

Soft and roomy, the high back suspension seat will keep you comfortable even on those extra-long mowing jobs. The seat slides a full 152 mm forward and back, letting you find just the right position for maximum personal comfort.



WIDE FOOT PAN

There's plenty of legroom up front, thanks to a wide foot pan. It also makes entry and exit a snap.

SMOOTH OPERATION LEVERS

The operation load of the dual operation levers can be adjusted to each operator's needs to provide smooth, precise control and less fatigue at the end of the day. The damper force can be easily adjusted to ensure optimum comfort for every operator.

ERGONOMIC CONTROL LAYOUT

All controls are ergonomically arranged for quick identification and simple operation, with most controls on the right side for faster, easier access.



127 mm DEEP WELDED MOWER DECK

This steel welded mower deck provides outstanding, professional-level cutting performance. A reinforced spindle mount area improves durability.



CUP HOLDER

Integrated cup holder ensures that your drink is always handy, so you can stay on the job longer between breaks.

LARGE FUEL TANK

The large, 25.7-litre fuel tank keeps the Z400 Series mowing for more than 6 hours between refueling stops. (depending on conditions)



*Photo shown with optional Operator Controlled Discharge Chute