4090.4E 4WD ROPS

Engine

SDF 1000 Series Tier 3 Diesel Engine 4 Cyl/4000cc Turbocharged Intercooled Liquid/Oil Cooled Engine speed programming Individual Bosch Injector Pumps 85Hp @ 2200 rpm (2005/25/CE) Side mounted upswept exhaust – Tractor only Side mounted down swept exhaust – Tractor + FEL 70lt Fuel Capacity

Transmission

30/15 Synchromesh Gearbox Forward/Reverse Synchro Shuttle Shuttle mounted on Steering Column Double Dry Heavy Duty 11" Clutch Gear Levers Located Right Hand Side Creep Gear Std Heavy Duty Rear Axle 4 Wheel Independent Braking Front Wheel Assist- Mechanical Front & Rear Diff Lock- Mechanical 40 km/h Road Speed

ΡΤΟ

Independent Rear PTO 540/ 750 Speed PTO 540 PTO @ 1967 Rpm 540E PTO @1560 Rpm 1"3/8 -6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment 320/70R24 Front 420/85R30 Rear Front Weight Frame Dynamic Steering Fenders



Operator Environment

2 Post ROP Frame Flat Floor ISO Mounted Platform Rubber Floor Mat Ergonomic Controls Telescopic and Tilting Steering Wheel Analogue Dash Deluxe PVC Mechanical Seat Sun Canopy Telescopic Mirrors 1 Rear Work lights 2 Bonnet Work lights Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System 42 I/min Hyd Pump Separate 17 L/min Steering Pump 3 Sets of Remotes Spring/Detent on 2 sets / 1 Set Float Mechanical Three Point Linkage EASYLIFT raise and lower switch Position & draft control Settings Cat 2 Ball ends 3500kg lift capacity Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3100kg

August 2021



W www.pfgaustralia.com.au P +61 (3) 8353 3600 A 199 Australis Drive, Derrimut, VIC 3026

