

Specifications

Model			KUBOTA					
			ZD1011	ZD1211	ZD1221	ZD1221L		
			ZD1011-54-AU	ZD1211-60-AU	ZD1221R-60R-AU	ZD1221L-72-AU	ZD1221RL-72R-AU	
Engine	Model		Kubota D782-E4-ZD-3	Kubota D1105-E4-ZD-2	Kubota D1305-E3-ZD-3			
	Type		Diesel, liquid-cooled (3 cyl.)					
	Max. horsepower (Gross)*	HP/rpm	19.3 @ 3200	24.8 @ 3000	29.1 @ 3000			
	Total displacement	cu.in. (cc)	47.5 (778)	68.5 (1123)	77.0 (1261)			
	Starting system		Key switch					
Dimensions	Overall length	mm	2230	2260		2380		
	Overall width	(w/ mower)	mm	1710	1875	1710	2180	1910
		(w/o mower)	mm	1210	1510		1540	
	Overall height	(w/ ROPS upright)	mm	1890	2000			
(w/ ROPS folded)		mm	1430	1640				
Wheel base		mm	1380	1440		1560		
Tyre / Tread	Front tread	mm	890	1064		1250		
	Rear tread	mm	930	1210				
	Tyre size	Front tyre		13×5.0-6 smooth pneumatic	15 × 6.5-8, smooth semi-pneumatic, low profile tyre			
Rear tyre			24 × 9.5-14, low profile tyre	26 × 12.0-16, low profile tyre				
Weight (w/ mower)		kg	600	760	765	790	805	
Transmission system	2-HST w/ Gear reduction							
Speed control	2-hand levers							
Travel speed range	Forward	km/h	0-14.5	0-17.0				
	Reverse	km/h	0-8.0	0-8.5				
Brake type	Wet multi disks, foot applied, released							
PTO	Type		Shaft drive					
	Clutch type		Hydraulic independent PTO clutch with wet multi disks					
	PTO brake		Wet single disk					
Mower deck	Model		RCK54P-1000Z	RCK60P-1200Z	RCK60RP-1200Z	RCK72P-1200Z	RCK72RP-1200Z	
	Mower deck type		Kubota ProDeck with ACS		Kubota ProDeck	Kubota ProDeck with ACS	Kubota ProDeck	
	Mower lift system		Hydraulic					
	Deck depth	in. (mm)	6.0 (152)		5.5 (140)	6.0 (152)	5.5 (140)	
	Belt type		Multi-belt					
	Deck steel thickness	in. (mm)	0.16 (4.2)				0.18 (4.5)	
	Anti-scalp roller		Rigid	Swivel				
	Cutting width of mower	in. (mm)	54 (1372)	60 (1524)		72 (1829)		
	Number of blades		3 blades					
	Cutting height	in. (mm)	1-5 (25-127)					
	Mounting system of mower		Quick joint, parallel linkage					
Blade tip speed (max.)	FPM (m/s)	17100 (87)	18000 (91)	16900 (86)	18000 (91)			
Seat		Delux suspension seat	Delux suspension seat with reclining and lumbar support					
Engine stop system	Key stop							
Fuel tank capacity	litres	23	49					
Battery	Maintenance free battery : 12 V, CCA : 430A, RC : 80 min							
Alternator capacity	AC Dynamo : 14 Amps @ 14 Volts							
Water temperature indicator	Standard							
Hour meter	Standard							
Fuel gauge	Standard							

*Power(HP) specifications for individual diesel engine models are rated pursuant to Society of Automobile Engineers(SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Diesel engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purpose only.

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

©2016 Kubota Corporation



KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic, 3029
 Freecall: 1800-334-653
 Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>

CB Norwood Distributors Ltd

PO Box 1265, 888 Tremaine Avenue,
 Palmerston North 0800 KUBOTA
 Tel: 06 356 4920 Fax: 06 356 4939

Web Site: <http://www.kubota.co.nz>